



ANTIMUFFA

Sanitizer anti – mould

Characteristic

ANTIMUFFA is a concentrated antiseptic for internal and external walls. Effectively sanitizes the masonry surfaces prior to the application of any paint, decorative coating with resinous base or wallpaper. ANTIMUFFA destroys the micro-organisms and the spores of vegetative forms.

Application

Dilute the product in reason of 1 to 20 with drinking water (1 Kg of ANTIMUFFA concentrated in 20 Kg of water).

For the walls without mycotic problems, apply a brush of ANTIMUFFA. Let it act for at least 6 – 8 hours prior to stretch the paint base.

For the walls with a presence of mycotic encrustations apply ANTIMUFFA on the surface to treat, let it act for few hours and remove the efflorescence through use of a sponge and pure water. Repeat the application of ANTIMUFFA, wait at least 6 – 8 hours prior proceeding to the finishing application.

Technical data

- | | |
|---------------------|--|
| • Packaging | Vase of 1 lt |
| • Specific weight | 1,00 Kg/lt \pm 0,10 |
| • Viscosity | 40 cPs |
| • Over coating | after 6 – 8 hours |
| • Consumption | according to the porosity of the support |
| • Conservation time | 12 months in an unopened package kept to a temperature over + 5° C |

Please note

The product suffers frost. Do not apply ANTIMUFFA with the air temperatures, of the support and of the product under to + 5° C and over to 40° C. Do protect the treated surfaces for at least 48 hours from rain. Do wash the equipment used straight after use. Please use rubber gloves during the application.