

EKOMARM Naxos Tonachello

Elastomeric based coating

Product:

EKOMARM NAXOS TONACHELLO is a continuous coat for external and internal mural surfaces with a base of acrylic polymers in water dispersion, oxides dyes, flour of quartz and marble granules. The type of binders used gives to the product both adequate resistance to alkali and the weather and applicability, workability and considerable adherence; the use of solid pigments to the light and alkali ensures the stability of colours even on walls particularly exposed to light radiations and weather. EKOMARM NAXOS TONACHELLO is suitable for use on agglomerations building consisting of plaster civilian of mortar lime or equivalent, plaster mortar lime of sand screened pulled to float finish, a gypsum plaster interior, precast cement conglomerates of concrete to compact, uniform and flat surfaces.

Preparation of the supports:

The new plasters have to be let to season for at least 4 – 6 weeks so that they neutralise in surface through natural carbonation. Even the newest patches must be left to season.

New wall surfaces: clean accurately, removing any trace of dust, dirt or the parts not perfectly adherent. Check that the wall is perfectly dry and apply, in case of very absorbent supports, pass a hand of EKOFOND B 200. Let elapse 8 hours and level the imperfections over the 3.0 mm of the surface with EKOCOLL.

Wall surfaces already painted and partially degraded: remove any trace of paint not perfectly adherent and eventual efflorescence; in presence of moulds it is appropriate to conduct a treatment with a sanitizing solution. Clean properly from dust and dirt, check that the wall is perfectly dry and fix the surface with a hand of EKOFOND B200. After 8 hours fill the big imperfections of the support with EKOCOLL.

Let elapse 24 hours and apply EKOMARM NAXOS TONACHELLO.

Application method

EKOMARM NAXOS TONACHELLO is ready to use and doesn't require dilution. Mix properly the product up to obtain an homogeneous mix and spread it in one hand with steel float. Balance it with a plastic float and prior that EKOMARM NAXOS TONACHELLO starts to film the surface, use the same tool to obtain the desired effect. Do not apply the product on sunny walls or in environmental temperature that could be below 5°C. After the application, the surfaces must be protected from heavy rain for at least 48 hours. Wash with water used tools immediately after use.

Technical data

- | | |
|--------------|------------------------------|
| ▪ Packaging | 20 kg bucket |
| ▪ Appearance | Pigment paste – white colour |



EKOMARM Naxos Tonachello

Elastomeric based coating

▪ Specific weight	1,9 ± 0,10 kg/l
▪ Average consumption per 1,2 cm of thickness	17 kg of powder/ m ²
▪ Dry extract	83% ± 0,10
▪ Granulometry	0.7 – 1,2 mm
▪ Permeability to water steam	μ<75

Please note:

**Do not apply on frozen supports, being thaw or where there is a chance of frost within 24 hours of application

**Do not apply the product on overheated surfaces, wet, in presence of strong wind or bright sunshine.

**Moisten the surfaces that must be treated

**Do not apply on inconsistent, dusty or friable supports, if not previously consolidated

**Protect the treated surfaces, for at least 24 hours, from heavy rain

**Do not leave the containers exposed to sunlight prior to use

**Wash with water the used equipment, straight after usage

Please note: All the above data relate to tests carried out in a controlled environment, and are therefore liable to change when the product is used.