

FINITURA PROTETTIVA EKOTOP LEVEL - S

PROTECTIVE FOR EKOTOP LEVEL

Characteristics

FINITURA PROTETTIVA EKOTOP LEVEL-S is a solvent-based, mono-component, ready to use product, specifically formulated for surface protection of **EKOTOP LEVEL**.

FINITURA PROTETTIVA EKOTOP LEVEL-S contains specific methacrylic resins with high temperature softening point, able to create a long lasting protection of the treated surface against water, oils and dirty absorption, reviving the surface colour at the same time.

FINITURA PROTETTIVA EKOTOP LEVEL-S is not turning yellow, is not sticky and is wash resistant

Application fields

Stain proof and hydro repellent treatment of **EKOTOP LEVEL**

Advantages

- It is a mono-component product, ready to use
- Thanks to its capacity of penetrating the substrate, it revives the colour of the surface.
- It is a specific, protective treatment of **EKOTOP LEVEL**
- It does not turn yellow
- It can be applied even on substrate not yet totally dry.

Suitable substrates

- **EKOTOP LEVEL** floor
- New generic mineral surfaces.

Substrate preparation

Substrate must be sound, homogeneous, free of dust, loose parts, oil, grease and anything that could prevent a uniform absorption of the product.

Application

FINITURA PROTETTIVA EKOTOP LEVEL-S is ready to use.

It must be applied by brush, or roller or low-pressure spraying in two crossed coats, of which the second one must be applied as soon as the first one becomes walkable. The product must be evenly spread on the surface without any standing puddles.

FINITURA PROTETTIVA EKOTOP LEVEL-S can be applied on **SAN MARCO FLOOR** the day after the smoothing of the floor, which must be properly cleaned from the dust using a vacuum cleaner. Wait for 24 hours at least before applying the wax-base products of Pietra di Venezia line.

Technical* and installation** data

* Appearance	Colourless Liquid
* Dilution	Ready to use
* Specific gravity	0,95 kg/l
* Average yeld (two coats)	0,2- 0,3 kg/m ²
* Application of the second coat	As soon as the first one is walkable
* Application temperature range	+5° C / +35° C
* Shelf life	12 months in original container, fresh and dry room protect from direct sunlight – It is damaged by frost

** Tools: brush, roller, low-pressure spray

Warning

** Do not apply on too warm surface, with strong wind and on sun-exposed substrate

** Do not apply on frozen substrate or when frost is forecasted in the next 24 hours

** Do not apply on incoherent or friable substrate or with loosing parts.

** Do not apply on dusty substrate.

** Avoid to freeze the product during the storage, at job-site or during the transport

** Wash the tools with solvent for nitro paints immediately after their use.

NB. The above data refer to tests carried out in controlled environment and could sensibly be modified by the job-site conditions.